Drains

## Variofix shallow bed upper sections with design cover



#### in ABS, incl. mesh fabric

design covers 🗆 120 mm and rim in stainless steel AISI 304, class K 3/L 15. For tile thickness of 8-21 mm, with or without Lock & Lift System

with Lock & Lift Art. #	` ′	<b>Oval</b> (Cl. L 15) 48 905	<b>Spot</b> (CI. K 3) 48 621	<b>Cross</b> (CI. K 3) 48 613	<b>Festival</b> (CI. K 3) 48 615	<b>Parade</b> (CI. K 3) 48 624	<b>Slot</b> (CI. K 3) <b>48 619</b>	<b>Sticks</b> (Cl. K 3) 48 617
without Lock & Lift Art. #	48 625	48 626	48 620	48 612	48 614	48 623	48 618	48 616

### Upper section with design cover



















#### in ABS

design covers 🗆 120 mm and rim in stainless steel AISI 304, class K 3 / L 15 with or without Lock & Lift System

		<b>Kessel</b> (Cl. L 15)	<b>Oval</b> (Cl. L 15)	<b>Spot</b> (CI. K 3)	<b>Cross</b> (CI. K 3)	<b>Festival</b> (CI. K 3)	<b>Parade</b> (Cl. K 3)	<b>Slot</b> (CI. K 3)	Sticks (CI. K 3)
with Lock & Lift A	rt.#	48 201	48 202	48 221	48 21 3	48 215	48 224	48 219	48 217
without Lock & Lift A	rt.#	48 225	48 226	48 220	48 212	48 21 4	48 223	48 218	48 216







# Hair filter

Art. # 48 700



# **Odour trap**

made of polymer for all upper sections System 125, Only for Ecoguss / Practicus sealing water height 50 mm according to norm

Art. # 48 600





Certification no. Z-19.17-1719



Certification no. Z-19.17-1719

#### Fire-Kit Fire protection insert

drains with vertical outlet and odour trap

Ø 58/78/83 Art. # 48 099 Ø **50/75** Art. # 48 099

Ø 110 Art. # 48 100

# Quick-Fit the passage seal

for core drillings for drain bodies with vertical outlet

\*with fire protection Art. # 48 990 (only in combination

with Fire-Kit protection insert)

without fire protection Art. # 48 991

#### Sludge trap

Multistop

odour, foam, rodent

and insect stop

Art. # 48 500

Art. # 48 168 see page 147

### All drain bodies: 1.8 l/sec flow rate Sealing water height 50 mm







#### **Practicus** in PP

with removable odour trap

Ø     B     H     Article #       50     245     120     45150       75     134     109     45170       110     148     92     45110       Vertical outlet       50     100     45250       75     110     45270	Lateral outlet						
75 134 109 45170 110 148 92 45110  Vertical outlet 50 100 45250	Ø	В	Н	Article #			
110 148 92 45 110 Vertical outlet 50 100 45 250	50	245	120	45 150			
Vertical outlet           50         100         45 250	75	134	109	45 170			
<b>50</b> 100 <b>45 250</b>	110	148	92	45 110			
	Vertical outlet						
75 110 <b>45 270</b>	50	10	00	45 250			
10 110 43210	75	11	10	45 270			
<b>110</b> 110 <b>45 210</b>	110	11	10	45 210			



#### Insulating body

fits all Ecoguss / Practicus drain bodies with vertical outlet

