





NEW Modular system with covers in stainless steel AISI 316L

Upper sections

Covers made fully from AISI 316L stainless steel - for high level corrosion resistance requirements!



in ABS...

with design covers □ 120 mm and rim in stainless steel AISI 316L, class L 15, with Lock & Lift System.
Art. # 48 203

in ABS...

with slotted cover/rim □ 138 mm in stainless steel AISI 316L, screwed, class L 15.
Art. # 48 205

in ABS, tileable...

□ 110 mm, made of polymer and rim in stainless steel AISI 316L, class K 3.
Art. # 48 207

in ABS...

with slotted cover □ 138 mm in stainless steel AISI 316L, screwed, class K 3.
Art. # 48 209



Multistop

odour, foam, rodent and insect stop
Art. # 48 500



Hair filter

made of polymer
Art. # 48 700



Odour trap

for all upper sections System 125, sealing water height 50 mm according to norm
Art. # 48 600



Fire-Kit Fire protection insert

Only for Ecoguss / Practicus drains with vertical outlet and odour trap
Certification no. Z-19.17-1719
Ø 58/78/83 Art. # 48 099
Ø 50/75 Art. # 48 099
Ø 110 Art. # 48 100



Quick-Fit the passage seal



for core drillings for drain bodies with vertical outlet

*with fire protection Art. # 48 990
(only in combination with Fire-Kit protection insert)
without fire protection Art. # 48 991

Sludge trap

Art. # 48 168 see page 147

All drain bodies:
1.8 l/sec flow rate
Sealing water height 50 mm



Practicus in PP

with removable odour trap

Lateral outlet

Ø	B	H	Article #
50	245	120	45 150
75	134	109	45 170
110	148	92	45 110

Vertical outlet

Ø	B	H	Article #
50	100	100	45 250
75	110	110	45 270
110	110	110	45 210




Insulating body

fits all Ecoguss / Practicus drain bodies with vertical outlet
Art. # 48 952

0.6 l/sec flow rate *)
Sealing water height 30 mm

1.0 l/sec flow rate *)
Sealing water height 30 mm

*) according to EN 1253 - 20 mm threshold




"The Ultraflat" in ABS

with sealing flange for shallow bed gasket,
with removable odour trap
Lateral outlet Ø 40,
Art. # 45 740



Lateral outlet Ø 50,
Art. # 45 750

1.2 l/sec flow rate *)
Sealing water height 50 mm



"The Vertical" in ABS

Vertical outlet Ø 50/40
with removable odour trap
fits all upper sections System 125
Art. # 45 254