Bathroom drains System 100

Classic			Products
Illustration and dimensioned drawing	Article description	Outer diameter Ø (mm)	Article #
	Bathroom drain <i>Classic</i> in ABS		
	with removable odour trap, sealing water height 50 mm, with fixed lip seal, with connection flange		
	With upper section in ABS		
	Lateral outlet		
130 1110 120 120 120 120 120 120 120 120 1	$\hfill \square$ with recessed polymer drain cover for on-site tiling 110 x 110 mm, class K 3	Ø 50 Ø 75	40 150.66 40 170.66
	□ with slotted cover 100 x 100 mm	Ø 50	40 150.20
	in stainless steel AISI 304, class K 3	Ø 75	40 170.20
	Vertical outlet	Ø 50	40.050.00
Illustration with tileable cover	with recessed polymer drain cover for on-site tiling 110 x 110 mm, class K 3	Ø 50 Ø 75	40 250.66 40 270.66
	□ with slotted cover 100 x 100 mm	Ø 50	40 250.20
	in stainless steel AISI 304, class K 3	Ø 75	40 270.20
0.8 l/sec flow rate Installation area 220 x 180 mm	LEAT Type-trained EN 1253		
© 200 □120 □120 □120 □120 □120 □120 □120 □	Bathroom drain <i>Classic</i> in ABS	□ Ø 50	40 150.30
	lateral outlet 2.5°/vertical outlet,	Ø 75	40 170.30
	with removable odour trap, sealing water height 50 mm, with fixed lip seal	2 Ø 50	40 250.30
1	Lateral outlet	Ø 75	40 270.30
0.8 l/sec flow rate	2 Vertical outlet		
Installation area 220 x 180 mm	Upper section with sealing flange		
. Ø 200	for use with 1 - 4 mm vinyl /		
138 mmin. 255 mman. 625	synthetic flooring with slotted cover made of polymer, grey, class K 3 (able to withstand loads up to max. 300 kg).		
2			
0.8 l/sec flow rate Installation area 180 x 180 mm	EN 1253		

Installation example Classic



The *Classic* bathroom drain ① is a compact bathroom drain which is available in many versions. It is available both with a vertical and a horizontal outlet ② in the sizes \varnothing 50 and \varnothing 75 mm. There is an adhesive flange ③ available as an option for humidity sealing. The cover is a stainless steel cover in an oval design ④ - but *Classic* bathroom drain can also be combined with any other upper section from the System 100 range.

Professional advantages

- Variable upper section rotatable, tiltable and height adjustable
- Sealing system safe to install
 The fixed lip seal reliably prevents the upper section from slipping
- With removable odour trap full access for maintenance and cleaning
- Flexible modular system with a large number of design covers.



SmartSelect makes planning quite simply quicker - visit smartselect.kessel.de for the configurator for alternative waterproofing layers in the system