Linearis			Products
Illustration and dimensioned drawing	Article description	Channel length	Article #
40 mm L: 750 / 850 / 950 / 1150 mm 140 mm 21. 06. 050	Shower channel <i>Linearis</i> in ABS with tileable access cover With bathroom drain body <i>Classic</i> in ABS, Ø 50, lateral outlet □ cover and rim in stainless steel AISI 304, class K 3, with seeping water opening	750 mm 850 mm 950 mm 1150 mm	40 150.83 40 150.84 40 150.85 40 150.87
Installation supports and mesh fabric included	0.4 l/sec flow rate with 10 mm threshold		
40 mm L: 750 / 850 / 950 / 1150 mm	Shower channel <i>Linearis</i> in ABS with tileable access cover With bathroom drain body "The Superflat" in PP, sound-absorbing, Ø 50, flexible lateral outlet, 1 inlet Ø 40 □ cover and rim in stainless steel AISI 304, class K 3, with seeping water opening	750 mm 850 mm 950 mm 1150 mm	42 701.83 42 701.84 42 701.85 42 701.87
Installation supports and mesh fabric included	0.4 l/sec flow rate with 10 mm threshold		

Installation example *Linearis*



The *Linearis* shower channel features a narrow, elegant stainless steel channel ① which can be discreetly integrated into the bathroom design. With a flow capacity of 24 liters per minute the *Linearis* shower channel is ideal for mounting against the wall at the back of the shower. For cleaning and maintenance purposes the stainless steel channel and tileable access opening ② can be removed allowing full access to the odor trap and drain body.

Professional advantages

- Flow rate 0.4 l/sec
- Extremely narrow and elegant channel
- Easy cleaning
 Access cover for easy cleaning
 and maintenance
- Particularly suitable for installation on the wall side
- Channel length: 750 mm, 850 mm, 950 mm, 1150 mm
- Flexible modular system with a large number of components.



SmartSelect makes planning quite simply quicker - visit smartselect.kessel.de for the configurator for alternative waterproofing layers in the system