Floor drains *Ferrofix* in stainless steel AISI 304 System 200



Floor drains <i>Ferrofix</i>			Accessories
Illustration and dimensioned drawing	Article description	Outer diameter Ø (mm)	Article #
□ 300 □ ∅ 180 = 1 □ 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Upper section in stainless steel AISI 304 □ with anti-slip drain cover 290 x 290 mm in stainless steel AISI 304, non-slip, class M 125* fits all drain bodies System 200	-	57 415
→ □ 300 → → ○ 180 → → ○ 180 → → ○ 200 →	Upper section in stainless steel AISI 304 ☐ with slotted cover 290 x 290 mm in stainless steel AISI 304, class M 125* fits all drain bodies System 200	-	57 425
□ 300 □ 200 → □ 300 □ 300 → □ 300	Upper section in stainless steel AISI 304 □ with round-slot cover plate 290 x 290 mm in stainless steel AISI 304, non-slip, class M 125* fits all drain bodies System 200	-	57 435
921	Extension section in PP, with lip seal on request also in AISI 304 / AISI 316L	-	48 988
Ø420 Ø220- Ø200- Ø200- Ø200-	Extension section in stainless steel AISI 304 with pressure sealing flange with connection flange	- -	27 185 27 186
	Odour trap in stainless steel AISI 304, removable, sealing water height 70 mm	-	27 182
Certification no. Z-19.17-1719	Fire-Kit 200 Fire protection insert can only be retrofitted for vertical drains Only use in combination with an odour trap	-	48 200
	Sludge trap in stainless steel AISI 304 ☐ Height 60 mm (H) ☐ Height 150 mm (H)		67 302 67 301
-Ø188- -Ø2	Sludge trap in PE-HD	-	67 300