

Floor drains *Ferrofix* with pressure sealing flange

Matrix order system / Products

Drain body	Upper sections			
<p><b>Floor drain <i>Ferrofix</i> in stainless steel AISI 304 with pressure sealing flange</b> with odour trap, connection to SML-pipe</p> <p><b>78mm</b> Ø 78: 142 Ø 110: 152 Ø 78: 105 Ø 110: 107 Ø 78: 110 Ø 110: 125</p> <p><b>110mm</b> Ø 273 Ø 132 Ø 78: 101 Ø 110: 87 201</p>	<p><b>Shallow bed upper section in ABS, with mesh fabric</b></p> <p>Ø 312 150 min. 10 max. 18 40 120 Ø 125</p> <p><b>with slotted cover</b> 138 x 138 mm and rim in stainless steel AISI 304, non-slip, class L 15, screwed</p> <p>Art. # <b>48 907</b></p>	<p><b>Shallow bed upper section in ABS, with mesh fabric</b></p> <p>Ø 312 150 min. 23 max. 40 40 120 Ø 125</p> <p><b>with anti-slip drain cover</b> 138 x 138 mm and rim in stainless steel AISI 304, non-slip, class L 15</p> <p>Art. # <b>48 965</b></p>	<p><b>Upper section in ABS</b></p> <p>138 138 125 125</p> <p><b>with slotted cover</b> 138 x 138 mm and rim in stainless steel AISI 304, non-slip, class L 15, screwed</p> <p>Art. # <b>48 176</b></p>	<p><b>Upper section in stainless steel AISI 304</b></p> <p>138 138 125 125</p> <p><b>with anti-slip drain cover</b> 138 x 138 mm in stainless steel AISI 304, class L 15 / M 125*</p> <p>* On-site lining work required</p> <p>Art. # <b>48 177</b></p>
<p>Ø 78</p>	<p><b>Complete drain comprising a combination of the drain body and upper section</b></p>			
<p>Lateral outlet Art. # <b>54 200</b></p>	<p><b>54 200.52</b></p>	<p><b>54 200.21</b></p>	<p><b>54 200.61</b></p>	<p><b>54 200.20</b></p>
<p>Vertical outlet Art. # <b>54 210</b></p>	<p><b>54 210.52</b></p>	<p><b>54 210.21</b></p>	<p><b>54 210.61</b></p>	<p><b>54 210.20</b></p>
<p>Ø 110</p>	<p><b>Complete drain comprising a combination of the drain body and upper section</b></p>			
<p>Lateral outlet Art. # <b>54 220</b></p>	<p><b>54 220.52</b></p>	<p><b>54 220.21</b></p>	<p><b>54 220.61</b></p>	<p><b>54 220.20</b></p>
<p>Vertical outlet Art. # <b>54 230</b></p>	<p><b>54 230.52</b></p>	<p><b>54 230.21</b></p>	<p><b>54 230.61</b></p>	<p><b>54 230.20</b></p>

\* Draining capacity valid for Ø 110 vertical outlet. Other variants 1.8 l/sec.



EN 1253

Accessories see page 194

4 Drains / channels in stainless steel